


300712F/TL/SB/24

Flat Lighting Body, Top Lighting & Side Bending



Output Power/Max Power	W	9.6W/Metre, 5 metres per reel
Input Rated Voltage	V	24V
Colour Temperature	K	6500K, 5700K, 4000K, 3000K, 2700K
Lumens	lm	275lm @ 5000K
Number of LEDs		120 Dot Free
LED Type		Lumileds 2835
Max Ambient Temperature (Ta)	°C	-40°C to +65°C
Working Temperature (Tc point)	°C	-40°C to +65°C
IP Protection Level		IP67 & Salt-mist proof
Dimensions	mm	W7.5 x H12
Max Length After Feed-in	m	5 metres Single End, 7.5 metres Double End
Cutting Unit Length		50mm
Bending Radius		30mm
Life Time		>50,000 Hrs
Material		Silicon
Detailed Description		Diffused flat lighting body and White reflector. Dual -colour silicon extrusion. UV & yellowish resistant. Horizontal bend.  UL 94 V-0. Easy installation and connection accessories.
Applications		Suitable for LED neon letters or signage, building and sign outline lighting, general and cove lighting. Ships, boats & vehicles. Bathroom and Spa lighting.
Other Information		E491839, UR Approved

## ADDITIONAL INFORMATION

Other colours: Red, Green, Blue, Yellow, RGB